

GT3000



MAIN FEATURES

1. Five fan speeds controlled by a Variable Frequency Drive for quiet operation
2. Exclusive Photo Catalytic Oxidation technology
3. Needlepoint and RF ion generation
4. Washable rear filter
5. Intelligent maintenance reminder
6. Adjustable purifier control – 250 to 3000 sq ft
7. Away Mode timer for high purification levels in unoccupied spaces
8. Full function remote control
9. Low Energy Consumption
10. Universal AC/DC power supply
11. Eliminates smoke, odors – doesn't cover them up
12. Significantly reduces mold, bacteria and viruses
13. Replaceable PCO cell and purification plate



WARRANTY

- 1 Year limited warranty

SPECIFICATIONS

- **Ozone output:** 360 mg/hr (Away Mode)
- **Technology:**
 - Needlepoint ionization
 - RF pulse ionization
 - Scalable Ozone generation
 - PCO technology (UV-C, Titanium Dioxide)
 - Adjustable 2, 4, 6, & 8-hour Away Mode
- **Electrical:** 100V-240V/50-60Hz 45W – can be operated anywhere in the world
- **Ozone Density:** <0.05mg/m³ (occupied condition), 1.5mg/m³ (unoccupied)
- **Ion generation:** 1 million/cubic cm
- **Coverage:** Up to 3000ft²
- **Display:** STN LCD

ELECTRICAL CERTIFICATIONS

UL (US and Canada), CE, PSE, TUV, EK (Korean)



PACKAGING

- Product Box
 - Color Printed Carton
 - Dimension (mm): 295X375X450
 - Weight (Kg): 5.5
- Master Box (Box for transport):
 - Single-color printed carton
 - Units per Box: 2
 - Dimension (mm): 610X390X470
 - Weight (Kg): 12